

TECHNICAL SPECIFICATION

Operation range	~40 m max. in open area
UHF channels	16 CH fixed
Frequency range about	{~606-690 MHz} nominal
Frequency step	500 kHz
ERP output	<10 mW
Modulation mode	digital frequency modulation
Oscillation	PLL synthesized
Frequency stability	±0,005 %
Microphone element	dynamic capsule
Characteristic	uni-directional
Handy charge in	USB-C port
Charging current	5 V ■ / 500 mA
Charging time	~2 h
Handy operation time	~6 h
Battery, Li-ion 18650	3.7 V / ~1200 mAh / ~4,4 Wh
Ta	5 °C...+35 °C
Handy dimensions	Ø53/33 x 255 mm
Weight	280 g



Antenna	flexible wire antenna
Modulation mode	digital frequency modulation
Oscillation	PLL synthesized
Frequency stability	±0,005 %
Audio frequency range	75 – 18.000 Hz
S / N ratio	>98 dB
THD	<0,9 % 1kHz
Audio output	~500 mV
Output connector	Ø6.3 mm mono plug
Receiver charge in	USB-C port
Charging current	5 V ■ / 500 mA
Charging time	~5 h
Operation time	~4.5 h
Battery, Li-ion AA size	3.7 V / ~800 mAh / ~3 Wh
Ta	5 °C...+35 °C
Receiver dimensions	30 x 93 x 30 mm
Weight	80 g

